RIDEWELL SUSPENSIONS

# *Ridewell's*
# Drum Brake Axle

*For trailers*

*Manufactured to Ridewell's stringent specifications*

*Straight and drop center beams available*

*Custom track widths available*

*16½" x 7" and 12¼" x 7½" brakes*

*Nominal wall thickness: ½", ⅝", & ¾"*

*Full range of hub and drum choices*

*Backed by a Ridewell warranty*

# Ridewell Drum Brake Axles - Specifications

**Application**
☐ Air Suspension ☐ Mechanical Spring Suspension

**Track**
☐ 71.5" ☐ 77.5" ☐ Other _____

**Beam Type**
☐ Straight ☐ 6.25" Drop
☐ 6.25" Inv. Drop ☐ 8.0" Drop

**Diameter**
☐ 5.00" ☐ 5.75"

**Wall Thickness**
☐ .47" ☐ .59" ☐ .75"

**Spindle**
☐ Tapered (FN) ☐ Parallel (FP)

**Brake Size**
☐ 16.5" x 7.0" ☐ 12.25" x 7.5" ☐ Other _____

**Brake Capacity**
☐ 20K ☐ 23K ☐ Other _____

**Brake Lining**
☐ Standard ☐ Extra Life

**Cam Enclosure**
☐ Yes ☐ No

**Wheel Data**
☐ Single ☐ Dual ☐ Steel
# of studs ____ Bolt Circle ____ ☐ Aluminum

**Hub & Drum**
☐ None ☐ Hub Piloted
☐ Stud Piloted ☐ Lightweight

**ABS**
☐ None ☐ Tone Ring ☐ Sensor

**Automatic Slack Adjustors**
☐ None ☐ Standard ☐ Other Brand _____

**Brake Chambers**
☐ None ☐ Type 24 ☐ Type 30
☐ Type 30/30 ☐ Other _____ Brand: ☐ STD ☐ Other _____

**Hub Caps/Bearings**
☐ Standard ☐ Other _____

**Seal Brand**
☐ Stemco Voyager (STD) ☐ Stemco Guardian ☐ Other _____

**Hub Lubricant**
☐ 80/90 Gear Oil (STD) ☐ Synthetic Oil (75W 90)
☐ Synthetic Grease (Hard) ☐ Synthetic Semi-Fluid Grease

**Dust Shields**
☐ Yes ☐ No

**PSI Tire Inflation**
☐ Prepped Standard ☐ Prepped Thermalert ☐ None

**Camber**
☐ Cambered ☐ Non-cambered

RIDEWELL SUSPENSIONS
P.O. Box 4586 ◆ Springfield, Missouri 65808
www.ridewellcorp.com ◆ 800.641.4122 ◆ Fax 417.833.4560